

OUTPUT RATINGS		50 Hz / 400 V	60 Hz / 480 V
Stand By Power		1020	
		816	
Prime Power		1100	
		880	

ENGINE TECHNICAL DATA	
Engine Model	Perkins 4008TAG2A
Number of Cylinders	6 / Inline
Cycle	4 Stroke
Bore / Stroke [mm] :	160 / 190
Induction :	Turbocharged CAC
Cooling Method :	Water
Governor Type :	Mechanical
Compression Ratio :	13,6:1
Displacement [lt] :	30,5
Electrical Sys. Voltage	24 / Negative
Battery Charger Amps	40

ALTERNATOR DATA		
Manufacturer	Maranello	
Model	M1100	
No. of Bearings :	Single	
Insulation Class:	H	
Winding Pitch :	2/3	
Number of Wire :	12	
Protection Class :	IP23	
Efficiency:	95,1%	
Voltage Regulation (Steady State) :	0,5%	
Total Harmonic Content:	3%	
Apparent Power (kVA)	1110	
Radiant Heat [Kw]:	50 Hz	
	60 Hz	

Dimension (WxHxL)	
CONOPIED	2468x3500x6078
OPEN SET	2050x2580x4500

WEIGHT (KG)	
CONOPIED	12220
OPEN SET	7585

FUEL TANK (LT)	
CONOPIED	2000
OPEN SET	2000

## AVAILABLE OPTIONS

AYPOWER offers a range of optional features to tailor our gensets to meet your power requirements.

Options:

- \* A wide range of Sound Attenuated Enclosures
- \* A variety of generating set control and synchronising panels
- \* Additional alarms and shutdowns
- \* A selection of exhaust silencer noise levels

For further information on all of the standard and optional features for this product, please contact AYPOWER or visit [www.aypowergenerator.com](http://www.aypowergenerator.com)

**Prime Rating:** These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

**Standby Rating:** These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standart reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.

