

OUTPUT RATINGS 50 Hz / 400 V 60 Hz / 480 V		
Stand By Power	150	TBA
	120	TBA
Prime Power	136	TBA
	100	TBA

ENGINE TECHNICAL DATA	
Engine Model	Ricardo - R6105AZLD
Number of Cylinders	6 / Inline
Cycle	4 Stroke
Bore / Stroke [mm] :	105 / 125
Induction :	Turbocharged
Cooling Method :	Water
Governor Type :	Mechanical
Compression Ratio :	16:1
Displacement [lt] :	6,49
Electrical Sys. Voltage	12 / Negatif
Battery Charger Amps	

ALTERNATOR DATA	
Manufacturer	Maranello
Model	M150
No. of Bearings :	Single
Insulation Class:	H
Winding Pitch :	2/3
Number of Wire :	12
Protection Class :	IP22/23
Efficiency:	93,8%
Voltage Regulation (Steady State) :	1,0%
Total Harmonic Content:	3,0%
Appreant Power (kVA)	10
Radiant Heat [Kw]:	50 Hz
	60 Hz

Dimension (WxHxL)	
CONOPIED	1100x2980x1860
OPEN SET	1100x2200x1700

WEIGHT (KG)	
CONOPIED	2200
OPEN SET	1680

FUEL TANK (LT)	
CONOPIED	340
OPEN SET	340

AVAILABLE OPTIONS

AYPOWER offers a range of optional features to tailor our gensets to meet your power requirements.

Options:

- * A wide range of Sound Attenuated Enclosures
- * A variety of generating set control and synchronising panels
- * Additional alarms and shutdowns
- * A selection of exhaust silencer noise levels

For further information on all of the standard and optional features for this product, please contact AYPOWER or visit www.aypowergenerator.com

Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure.No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standart reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.

